

Refrigerant Recovery

Cylinders



Refrigerant Recovery



Cylinders



AMTROL's Refrigerant Recovery Cylinders are the product of over 35 years of refrigerant cylinder manufacturing expertise. Our cylinder manufacturing facilities were the first in the industry to receive the internationally recognized **ISO 9001 Registration**. Our cylinders are designed for use with CFC, HCFC and HFC recovered or virgin refrigerants.

Features and Benefits

- Powder coated cylinders for a high gloss, durable finish.
- Precharged cylinders assure a clean dry interior.
- Dual Port Liquid/Vapor Valve is standard on all cylinders.
- Valving options for many liquid and vapor applications.
- Backed by **AMTROL®** total quality assurance.
- Reusable and conforms to DOT-4BA specifications and ARI Guidelines.
- Unique collar design for ease of handling.

Configuration	Water Capacity		Volume Cubic	Tare Weight
	Inches mm	lbs. kg.	Gal. liter	Inches cubic centimeters
	26.1	3.1	723.8	17.6
	47.7	5.7	1322.7	28.5

Collar O.D. is 7 1/4" (184.2 mm)
Foot ring O.D. is 7 3/4" (197 mm)
Dimensions and capacities are approximate

Service Pressure 400 psig 27.6 Bar
Minimum Burst Pressure 800 psig 55.2 Bar



www.amtrol.com

Corporate Headquarters, Cylinder Sales Department
1400 Division Road, West Warwick, RI 02893-2300
Telephone: 800-736-1149 / 401-884-6300
FAX: 401-884-5276

Part# 9024-044 (06/09)
MC# 8210